# This Page Is Inserted by IFW Operations and is not a part of the Official Record

# **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

# IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents will not correct images, please do not report the images to the Image Problem Mailbox.

#### **PCT**

# WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:
G07F 17/32
A1
(11) International Publication Number: WO 97/19428
(43) International Publication Date: 29 May 1997 (29.05.97)

(21) International Application Number: PCT/GB96/02869

(22) International Filing Date: 21 November 1996 (21.11.96)

(30) Priority Data:

95/9857

21 November 1995 (21.11.95) ZA

(71) Applicant (for 1S only): BROWN, Keith, Edwin, Frank [GB/ZA]; 40 Iona Drive, Hurlingham, Sandton, 2146 (ZA).


(71)(72) Applicants and Inventors (for all designated States except IS): BELAMANT, Serge, Christian, Pierre [FR/ZA]; 43 Carlisle Avenue, Hurlingham, Sandton, 2196 (ZA). SHENKER, Gavin [ZA/ZA]; 11 Viljoen Street, Rouxville, Johannesburg, 2192 (ZA).

(74) Agent: BUTLER, Michael, John; Frank B. Dehn & Co., 179 Queen Victoria Street, London EC4V 4EL (GB). (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

#### **Published**

With international search report.

(54) Title: METHOD AND APPARATUS FOR CONTROLLING A GAMING OPERATION



#### (57) Abstract

A system for controlling a game operation comprises a secure processing and memory apparatus (10) in the form of a smart card, together with non-secure input (26) and display (36) means connectable to the smart card. The memory (18, 20, 22) of the smart card (10) stores software controlling the operation of the game and also data relating to gains or losses of the player. Input signals generated by the player are processed within the secure processor (14) and all operations which can influence the outcome of the game are carried out within the secure processor (14) so that the system is not susceptible to tampering, even when used in a non-secure environment. Thus, the system allows gaming to take place in hotel rooms and other non-secure locations, with secure betting and allocation of winnings.

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
ΑU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	Œ	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	ŁK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

- 1 -

# METHOD AND APPARATUS FOR CONTROLLING A GAMING OPERATION

#### **BACKGROUND OF THE INVENTION**

THIS invention relates to a method of securely controlling a gaming operation and to a system and apparatus for implementing the method.

Games of chance in which a player actively participates in the game and can win money according to the outcome of the game are very popular. Such games are normally played in casinos or other controlled environments.

Electromechanical and electronic gaming apparatus is frequently used, but must generally also be located in a secure environment to prevent tampering with the apparatus. For example, in the case of an electronic gaming apparatus, a person with uncontrolled access to conventional equipment could monitor the flow of data in the equipment and interfere with its operation, for example, by transmitting false instructions to credit a player's account with winnings.

It is an object of the invention to provide a method of and apparatus for controlling a gaming operation which can be operated safely in a non-secure environment.

#### SUMMARY OF THE INVENTION

According to the invention there is provided a method of controlling a gaming operation in which a player bets on the outcome of a game, the method comprising:

providing secure apparatus comprising secure processor means and associated secure memory means;

storing in the secure memory means first data related to the control and operation of a game and second data relating to gains or losses of a player of the game;

transmitting input signals to the secure processor means from input means operated by the player; and

transmitting output signals from the secure processor means to display means,

wherein the result of the game and the allocation of gains or losses to the player are controlled by operations performed on the stored first and second data and on data derived from the input signals, in the secure apparatus.

Further according to the invention there is provided a system for controlling a gaming operation in which a player bets on the outcome of a game, the system comprising:

secure apparatus comprising secure processor means with associated

- 3 -

secure memory means;

input means connectable to the secure processor means and operable by a player of a game to transmit input signals to the secure processor means;

display means connectable to the secure processor means for receiving output signals from the secure processor means representing a result of the game;

wherein the secure memory means stores first data related to the control and operation of a game and second data relating to gains or losses of the player, and wherein the result of the game and the allocation of gains or losses to the player are controlled by operations performed on the stored first and second data and on data derived from the input signals, in the secure apparatus.

The secure processor means and the secure memory means are preferably provided together on a "smart card" comprising a substrate supporting the processor and memory means, associated electronic circuitry, and contact means for permitting communication between the processor means and the input and display means.

The input means may be, for example, a keyboard of a computer, a keypad of a telephone, or a keypad on a dedicated games apparatus.

Alternatively, the input means may comprise a "touch screen" display, a mouse, or any other input device with a sufficient number of output states.

- 4 -

The display means may comprise, for example, a television set, a video display unit or monitor, a liquid crystal display or another display.

The secure memory means may include first memory for storing software controlling and operating the game, and second memory storing results of the game and data representing the value of gains or losses of the player which is adjusted according to the outcome of the game.

The invention extends to the secure apparatus of the system.

#### BRIEF DESCRIPTION OF THE DRAWINGS

- Figure 1 is a simplified block schematic diagram of secure apparatus for controlling a gaming operation according to the invention;
- Figure 2 is a block schematic diagram showing a gaming system in which the secure apparatus of Figure 1 is used together with associated non-secure apparatus; and
- Figures 3 are flow charts indicating the operation of the secure

  to 6 apparatus with regard to the playing of a game of chance and
  the management of a credit balance of a player, with the
  corresponding operation of the non-secure apparatus
  indicated.

#### **DESCRIPTION OF EMBODIMENTS**

Referring first to Figures 1 and 2, the heart of the present invention is a secure apparatus comprising a "smart card" 10 with a contact pad 12. The circuitry of the smart card is illustrated in greater detail in Figure 1, and includes a central processing unit (CPU) 14, which is connected via an internal bus 16 to associated random access memory (RAM) 18, read only memory (ROM) 20 and an electrically erasable programmable read only memory (EEPROM) 22. The CPU 14 is also connected via the bus 16 to a serial input/output interface 24 and a random number generator circuit 26. The contact pad 12 includes power supply contacts 12.1 and 12.2 which supply power to the circuitry of the smart card, a clock contact 12.3 connected to the CPU 14 which supplies an external clock signal to the circuitry, and an input/output (I/O) contact 12.4 allowing communication between the serial interface 24 and an external device.

The ROM 20 stores software which controls the operation of one or more games which can be played by a user of the apparatus, as well as controlling the management of winnings data relating to gains and losses for that player arising out of bets placed by the player on the outcome of a game. The RAM 18 temporarily stores data generated for the playing of the game, the abovementioned winnings data, and associated data. The EEPROM 22 stores data which may be changed from time to time, which may include a portion of the software stored in the ROM 20, or even the entire software, as well as the required operational parameters. For example, a portion of the software stored in the EEPROM 22 which may be adjusted from time to time could be used to enhance the functionality of the game. Alternatively, the data in the EEPROM could be adjusted to update the payout values of

- 6 -

the game.

The simplified schematic diagram of Figure 2 is an example of one embodiment of a gaming system which uses the smart-card based secure apparatus of Figure 1 to implement a gaming operation. The system includes an input device in the form of a keypad or keyboard 26 which is connected to a microprocessor-based controller 28. In the prototype system, the keypad 26 is a dedicated unit, similar in appearance to a remote control for a television set and which has a numeric keypad 30 as well as cursor keys 32. The communication link 34 between the keypad 26 and the controller 28 may comprise a cable but is preferably a wireless link, such as an infrared link.

Connected to the controller 28 is a display 36, which in the prototype system is a conventional television set. Thus, the output of the controller 28 is a modulated RF signal which can be received by a conventional television set. Obviously, depending of the nature of the display 36, the output of the controller 28 will vary.

Connected to the controller 28 is a smart card reader 38 which has contacts corresponding to the contact pad 12 on the smart card 10 which supplies the necessary power and clock signals to the smart card, and which permits communication between the I/O interface 24 of the smart card and the microprocessor of the controller 28.

It should be appreciated that the components of the system shown in Figure 2, apart from the secure apparatus 10, need not be secure themselves, nor need they be located in a secure environment.

- 7 -

The operation of the system will now be described. The essence of the invention is that a gambling game, in which value is purchased to be bet by a player of a game using the secure apparatus and in which winnings accrue to or losses are debited from the player, depending on the outcome of the game, is operated securely in a non-secure environment. This is achieved by providing apparatus which has a secure processor and associated secure memory, with all crucial operations relating to the outcome of the game and the crediting of winnings or the debiting of losses to the player being carried out internally between the secure processor and the secure memory only. This prevents tampering with the apparatus, so that neither the outcome of the game nor the winnings or credit balance of the player can be tampered with.

In the prototype system, the game offered is five card poker. The described system allows a player to effectively deposit value into the secure apparatus, creating a credit balance, to place bets while playing the game offered (one or more times), and to accrue winnings (or losses) according to the outcome of each game. Eventually, the player can convert the winnings (if any) into value.

In the prototype system, a user of the system obtains a smart card 10 which is loaded with either a predetermined credit value or a credit value selected by the user, and which is either paid for or debited to an account of the player, for example in a club or hotel. The user inserts the smart card 10 into the card reader 38 of the system, which may be installed in a hotel room for example.

Referring now to the flow chart of Figure 3, the CPU of the smart card reads

and outputs the credit balance stored in the EEPROM 22 of the card to the controller 28 which generates a display on the display unit 36. This allows the user to see what the maximum possible bet is. The user then decides how much to bet on the game to be played, and inputs this figure via the keypad 26. The secure apparatus will not allow a bet greater than the credit balance available. The amount bet is deducted from the credit balance before the game commences.

A "deck of cards" is created by the software stored in the ROM 20 or the EEPROM 22 with the aid of the native random number generator circuit 26 and "shuffled" numerous times in order to ensure that the sequence of cards cannot be predicted. The first five cards from the deck of cards are moved into a "hand" dealt to the user and stored in the RAM 18, and five bytes of data representing the hand are output so that the hand is displayed to the user. The user can now decide which "cards" in the hand to retain or discard in order to attempt to improve the displayed hand.

Referring now to Figure 4, the user operates the keypad to indicate which cards are to be discarded or retained. This choice is indicated by five bytes, each of which relates to a card in the hand dealt and which could be either high or low values.

A high value indicates that the card in question must be retained, while a low value indicates that the card must be discarded. For each card that must be discarded, the next card within the deck of cards is moved into the vacated position within the hand dealt. This sequence of cards now becomes the final hand dealt and is compared by the CPU 14 to all possible winning hands, from the highest possible win downwards (eg. royal flush, four of a

- 9 -

kind, ....., two pairs, one pair).

As soon as the hand dealt is found to match a winning hand, a predetermined payout value (stored in the EEPROM 22) for that particular winning hand is multiplied by a value corresponding to the amount bet (units bet) and the result is stored in the RAM 18. If no winning hand is found, the whole of the RAM 18 is cleared, including the data corresponding to the amount bet (units bet). The bytes representing the final hand dealt and the remaining units bet are output to the display. If the units bet value is zero, a new game must be started and a new amount bet. Otherwise, the user can decide to double the units bet or to add them to the stored credit balance.

Referring to Figures 5 and 6, operation of the keypad by the user inputs a byte having a high value or a low value, depending on whether the user wishes to double the bet or to add the units bet value to the existing credit balance. Action is only taken by the CPU 14 if the units bet value is other than zero. If the byte has a low value, the units bet value is added to the credit balance and the whole of the RAM 18 including the units bet register is cleared. If the byte has a high value, any five cards from the deck of cards are randomly moved into the hand dealt and only the first card of the hand dealt is output. This card is displayed, together with four blank cards. The user decides which of these blank cards might be higher or the same as the card displayed, and selects a card using the keypad 26, which inputs a byte with a value between one and four. An action is only taken on this byte if the user had previously requested a doubling of the bet.

The selected card is compared to the card output from the hand dealt. If the numerical value of the card chosen is greater than the numerical value of the

- 10 -

card output, the units bet value is doubled. If the numerical value of the card chosen is equal to the numerical value of the card output there is no change to the units bet value. If the numerical value of the cards chosen is less than the numerical value of the card output, the whole of the RAM 18 including the units bet register is cleared.

The bytes representing the five cards including the card output stored in the hand dealt and the value remaining in the units bet register are output and displayed. If no value remains in the units bet register, a new game must be started, or else the player can repeat the above process, either attempting to double the units bet value or adding the units bet value to the credit balance.

The flow charts of Figures 3 to 6 also illustrate the operations which are provided by the non-secure components of the system.

In the prototype system, the RAM 18 layout had the following configuration:

*Units bet	4 bytes	Between 1 and JACKPOT units.
		Indicates the amount of units bet or
		won.
*Deck of cards	52 bytes	Each card of the deck is represented by
		1 byte.
*Hand dealt	5 bytes	Each card in the deal is represented by
		l byte.

The byte representing each card is split into 2 nibbles i.e. the higher order nibble denoting the suit (eg 0001b = spades, 0010b = hearts, 0100b =

- 11 -

diamonds and 1000b = clubs) and the low order nibble denoting the card within the suit (eg 0001b = ace, 0010b = two, 0011b = three .... 1010b = ten, 1011b = jack, 1100b = queen, 1101b = king). As an example the four of clubs would be represented by the byte 84h (10000100b) and the king of spades would be represented by the byte 1Dh (00011101b).

In the prototype system, the EEPROM 22 stores the necessary logic and algorithms required to emulate a standard five card poker game.

The layout of the rest of the EEPROM 22 for any game of chance could be as follows:

*Balance of units 4 b	ytes E	Between 1 and	42 000 000
-----------------------	--------	---------------	------------

or credit balance units

\*Payout values variable These values depend on the

game of chance being played and upon the return expected by the operator of the system.

The balance of units field is updated every time a game is played, while the payout values are set before the card is issued to the user and would not normally be altered.

From the above description it will be apparent that, although there is communication between the secure processor of the smart card and external input and display means, this communication concerns only output signals from the secure processor which generate a display, and permissible control signals generated by the keypad or other input means which is operated by

- 12 -

the user of the system. There is no bus or other communications link which is accessible to a would-be hacker or criminal which could be accessed to tamper or interfere with the operation of the system. Thus, the described invention allows for the secure operation of a gambling game in which money or its equivalent is won or lost, which can safely be used in a non-secure environment.

- 13 -

#### **CLAIMS**:

1. A method of controlling a gaming operation in which a player bets on the outcome of a game, the method comprising:

providing secure apparatus comprising secure processor means and associated secure memory means;

storing in the secure memory means first data related to the control and operation of a game and second data relating to gains or losses of a player of the game;

transmitting input signals to the secure processor means from input means operated by the player; and

transmitting output signals from the secure processor means to display means,

wherein the result of the game and the allocation of gains or losses to the player are controlled by operations performed on the stored first and second data and on data derived from the input signals, in the secure apparatus.

2. A system for controlling a gaming operation in which a player bets on the outcome of a game, the system comprising:

secure apparatus comprising secure processor means with associated secure memory means;

input means connectable to the secure processor means and operable by a player of a game to transmit input signals to the secure processor means;

display means connectable to the secure processor means for receiving output signals from the secure processor means representing a result of the game;

wherein the secure memory means stores first data related to the control and operation of a game and second data relating to gains or losses of the player, and wherein the result of the game and the allocation of gains or losses to the player are controlled by operations performed on the stored first and second data and on data derived from the input signals, in the secure apparatus.


- 3. A system according to claim 2 wherein the secure processor means and the secure memory means are provided together on a "smart card" comprising a substrate supporting the processor and memory means, associated electronic circuitry, and contact means for permitting communication between the processor means and the input and display means.
- 4. A system according to claim 2 or claim 3 wherein the input means is a keyboard of a computer, a keypad of a telephone, or a keypad on a dedicated games apparatus.
- 5. A system according to claim 2 or claim 3 wherein the input means

comprises a "touch screen" display.

- 6. A system according to claim 2 or claim 3 wherein the input means comprises a mouse.
- A system according to any one of claims 2 to 6 wherein the display means comprises a television set, a video display unit or monitor or a liquid crystal display.
- 8. A system according to any one of claims 2 to 7 wherein the secure memory means includes first memory for storing software controlling and operating the game, and second memory storing results of the game and data representing the value of gains or losses of the player which is adjusted according to the outcome of the game.
- 9. Secure apparatus for use in a system for controlling a gaming operation in which a player bets on the outcome of a game, the secure apparatus comprising secure processor means with associated secure memory means, wherein the secure memory means stores first data related to the control and operation of a game and second data relating to gains or losses of the player, and wherein the result of the game and the allocation of gains or losses to the player are controlled by operations performed on the stored first and second data and on data derived from the input signals, in the secure apparatus, the secure processor means being adapted for connection to input means operable by a player of a game to transmit input signals to the secure processor means, and further being adapted for connection to display means arranged to receive output signals from the secure processor

- 16 -

means representing a result of the game.



**E38** 1

12 28 DISPLAY

12 28 36

CARD READER CONTROLLER 26


KEYPAD/KEYBOARD A

30 32

SUBSTITUTE SHEET (RULE 26)

#### NON-SECURE COMPONENTS


## SECURE SMART CARD +



SUBSTITUTE SHEET (RULE 26)

#### NON-SECURE COMPONENTS


#### SECURE SMART CARD



SUBSTITUTE SHEET (RULE 26)

#### NON-SECURE COMPONENTS

#### SECURE SMART CARD




SUBSTITUTE SHEET (RULE 26)

#### \_===6

# NON-SECURE COMPONENTS

#### SECURE SMART CARD



Int ronal Application No PCT/GB 96/02869

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 G07F17/32	
According to International Patent Classification (IPC) or to both national classification and If B. FIELDS SEARCHED	PC
Minimum documentation searched (classification system followed by classification symbols)	
IPC 6 G07F	
Documentation searched other than minimum documentation to the extent that such document	ts are included in the fields searched
Electronic data base consulted during the international search (name of data base and, where p	practical, search terms used)
	·
C. DOCUMENTS CONSIDERED TO BE RELEVANT	
Category Citation of document, with indication, where appropriate, of the relevant passage	Relevant to claim No.
X W0 92 10806 A (GTECH) 25 June 1992 see page 14, line 11 - line 25; figure 3	1-4,7-9 5
Y EP 0 588 625 A (BARCREST) 23 March 1994 see abstract	5
X US 4 764 666 A (BERGERON) 16 August 1988 see column 6, line 19 - line 58; figures 1-4	1-4,7-9
X EP 0 596 760 A (INFO TELECOM ET AL.) 11 May 1994 see column 9, line 9 - line 43; figures	1,2,4, 7-9
X EP 0 360 613 A (BALLY MANUFACRUTING) 28 March 1990 see column 4, line 29 - line 57 see abstract; figures	1-3,7-9
-/	
X Further documents are listed in the continuation of box C. X Patent	family members are listed in annex.
Special categories of cited documents:	ment published after the international filing date
'A' document defining the general state of the art which is not	y date and not in conflict with the application but inderstand the principle or theory underlying the
considered to be of particular relevance invention  E' earlier document but published on or after the international 'X' document	of particular relevance; the claimed invention
L' double in the day throw doubts on priority claim(s) or involve an	considered novel or cannot be considered to a inventive step when the document is taken alone
citation or other special reason (as specified) cannot be	of particular relevance; the claimed invention considered to involve an inventive step when the
other means ments, aug	is combined with one or more other such docu- th combination being obvious to a person skilled
r occurrent patriates prior to sie international ming date out	member of the same patent family
Date of the actual completion of the international search Date of ma	ulling of the international search report
25 February 1997	12. 03. 97
Name and mailing address of the ISA Authorized	officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rigwijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,	ville, D

In tional Application No PCT/GB 96/02869

		PCT/GB 96/02869
	auon) DOCUMENTS CONSIDERED TO BE RELEVANT	
ategory *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 2 287 342 A (WALKER ASSET MANAGEMENT) 13 September 1995 see page 14, line 21 - page 15, line 6; figure 3	1,2,4, 7-9
X	DE 41 35 767 A (ADP-AUTOMATEN) 13 May 1993 see column 2, line 47 - line 65 see abstract; figures	1,2,8,9
A	GB 2 267 772 A (PCP MICRO PRODUCTS) 15 December 1993 see abstract; figures	6

1

Information on patent family members

In tonal Application No
PUT/GB 96/02869

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9210806 A	25-06-92	US 5276312 A AU 9153591 A BR 9107145 A OA 9782 A	04-01-94 08-07-92 19-04-94 15-04-94
EP 588625 A	23-03-94	GB 2270787 A DE 69301214 D DE 69301214 T	23-03-94 15-02-96 29-08-96
US 4764666 A	16-08-88	AU 2218688 A CA 1294052 A DE 3877868 A EP 0307925 A JP 1222374 A US 4882473 A	23-03-89 07-01-92 11-03-93 22-03-89 05-09-89 21-11-89
EP 596760 A	11-05-94	FR 2697653 A AU 663224 B AU 4745993 A BR 9303955 A CA 2107249 A CN 1086455 A JP 6315573 A US 5507489 A ZA 9307230 A	06-05-94 28-09-95 19-05-94 24-05-94 05-05-94 11-05-94 15-11-94 16-04-96 29-03-95
EP 360613 A	28-03-90	US 5179517 A AT 116754 T AU 613484 B AU 3450489 A DE 68920391 D DE 68920391 T	12-01-93 15-01-95 01-08-91 29-03-90 16-02-95 27-07-95
GB 2287342 A	13-09-95	AU 8025494 A BR 9405271 A CA 2137498 A CN 1122032 A DE 4437277 A DK 11395 A FI 950950 A	21-09-95 17-10-95 12-09-95 08-05-96 14-09-95 12-09-95

Information on patent family members

In "tional Application No PCT/GB 96/02869

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2287342 A		FR 2717283 A	15-09-95
		HU 71560 A	28 <b>-</b> 12-95
		IE 950162 A	20-09-95
		IT MI950164 A	11-09-95
		JP 7255950 A	09-10-95
		LU 88582 A	18-03-96
		MC 2402 A	26-07-96
		NL 9402220 A	02-10-95
		NO 950746 A	12-09-95
		OA 9971 A	11-12-95
		PL 307582 A	18-09-95
		PT 101671 A	12-09-95
		SE 9500437 A	12-09-95
		WO 9524689 A	14-09-95
		AU 2953195 A	25-01-96
		WO 9600950 A	11-01-96
		ZA 9505451 A	13-02-96
DE 4135767 A	13-05-93	NONE	
GB 2267772 A	15-12-93	NONE	